

Corner Radius - Long Shank - 2 flutes



● Micro Grain Carbide

● WC=90 Co=10 HV30=1571 Rupture=3750N/mm² Grain Size=0.6μm



MODE	Diameter	Corner Radius	Flute Length	Full Length	Shank Diameter	Flutes
	d	R	l	L	D	Z
LRTA030032 AlTiN	3	0.3	8	75	3	2
LRTA030052 AlTiN	3	0.5	8	75	3	2
LRTA030102 AlTiN	3	1	8	75	3	2
LRTA040032 AlTiN	4	0.3	10	75	4	2
LRTA040052 AlTiN	4	0.5	10	75	4	2
LRTA040102 AlTiN	4	1	10	75	4	2
LRTA040152 AlTiN	4	1.5	10	75	4	2
LRTA060032 AlTiN	6	0.3	15	100	6	2
LRTA060052 AlTiN	6	0.5	15	100	6	2
LRTA060102 AlTiN	6	1	15	100	6	2
LRTA060152 AlTiN	6	1.5	15	100	6	2
LRTA060202 AlTiN	6	2	15	100	6	2
LRTA080032 AlTiN	8	0.3	20	100	8	2
LRTA080052 AlTiN	8	0.5	20	100	8	2
LRTA080102 AlTiN	8	1	20	100	8	2
LRTA080152 AlTiN	8	1.5	20	100	8	2
LRTA080202 AlTiN	8	2	20	100	8	2
LRTA080252 AlTiN	8	2.5	20	100	8	2
LRTA080302 AlTiN	8	3	20	100	8	2
LRTA100032 AlTiN	10	0.3	25	100	10	2
LRTA100052 AlTiN	10	0.5	25	100	10	2
LRTA100102 AlTiN	10	1	25	100	10	2
LRTA100152 AlTiN	10	1.5	25	100	10	2
LRTA100202 AlTiN	10	2	25	100	10	2
LRTA100252 AlTiN	10	2.5	25	100	10	2
LRTA100302 AlTiN	10	3	25	100	10	2
LRTA120032 AlTiN	12	0.3	30	100	12	2
LRTA120052 AlTiN	12	0.5	30	100	12	2
LRTA120102 AlTiN	12	1	30	100	12	2
LRTA120152 AlTiN	12	1.5	30	100	12	2
LRTA120202 AlTiN	12	2	30	100	12	2
LRTA120252 AlTiN	12	2.5	30	100	12	2
LRTA120302 AlTiN	12	3	30	100	12	2

Application :

◎ Recommend

○ Suitable

X Not Recommend

carbon steel, Alloy steel	Pre-hardened steel	High-hardened					Stainless steel	Copper alloy	Aluminun alloy
	~45HRC	~50HRC	~55HRC	~60HRC	~65HRC				
○	◎	◎	○			○			